INFINITY RANGE

YCXL R

PASS-THROUGH UNIT

DESCRIPTION

Multipurpose Washer - 600x500mm rack - upper control panel - stainless steel wash and rinse system - Built-in dosing units and drain pump - RCD: rinse control device as a standard. Wi-Fi connectivity and “Comenda Cloud Washing” App and Web Portal for remote monitoring.

STANDARD FEATURES

RELIABLE.

- AISI 304 stainless steel execution;
- Fully enclosed back of the machine;
- **Double wall insulated hood.**

SIMPLE.

- Full touchscreen graphic interface;
- 5 different programming options;
- Electronic adjustment of the detergent and rinse aid dosing pumps from the control panel;
- Simplified diagnostics: three different colors to show the type of alarm in progress;
- The intuitive START button features clear cycle monitoring with colour-coded status indicatoris to help your operations to run at its best;

HYGIENE.

- **TH LABEL program is standard for all infinty models;**
- Partial water draining before rinsing;
- RCD- Rinse Control Device;
- Self-cleaning cycle at unit switch-off;
- Removable rack guide;
- Single piece deep drawn tank;
- Self-draining wash pump;
- Triple filtration system (stainless steel surface filter, polypropylene basket filter and stainless steel mesh wire micro-filter).

FLEXIBILE.

- Buil-in drain pump and perhistaltic dosing units
- Provision for peak power reduction connection (PCE)
- Multivoltage (three phase only)

YCXL R

STANDARD FATURES

WI-FI AND BLUETOOTH CONNECTIVITY & REMOTE MONITORING

The new Wi-Fi and Bluetooth Pack allows the operator to easy monitoring the machine functions and access a vast amount of information; prevent possible failures by managing the anomalies in real time from smartphone, tablet and PC and keep consumptions under control.

COMENDA CLOUD WASHING APP E WEB PORTAL

Simple and intuitive gives you the power to:

- Check the main operating parameters of the unit;
- Start/stop the washing cycle;
- Download Records and HACCP reports;
- Access the alarm list and manage the anomalies;
- Check and download technical documentation;
- Save unit specific parameters or data settings;
- Adjust temperatures and dosage for chemicals;
- Plan the calls out for fixing only if necessary;
- Develop periodic reports for the end user;
- Make a remote assessment of wear parts

STANDARD RACK EQUIPMENT

RACKS AND INSERTS

- XLP: 1 Combination rack XLB 500x600mm
- XLB : 1 Rack for 24 dishes XLP 500x600mm
- 1 600x500 mm rack for 5 bake pans
- 1 cutlery holder

XLB

XLP



YCXL R

OPTIONAL

- 9 kW booster
- Detergent and rinse aid level probe kit
- Entry and exit table
- Water softener - external
- Reverse osmosis unit - external
- CRC2- heat recovery unit: CRC2 allows for cold water connection (15 to 30 deg C). CRC2 allows for consistent energy savings. Minimizing the steam released, CRC2 helps creating a more comfortable work environment.
- MOVE - AUTOMATIC HOOD LIFT SYSTEM:
  1. Automatic hood lifting at the end of the cycle to guarantee perfect sanitisation of the crockery
  2. Hands-free foot trigger to activate the automatic hood closure
  3. Emergency stop button
  4. Additional push buttons to open and close the hood
  5. Obastacles detection
  6. during hood closing for the maximum operator’s safety
- AS6 LI - STANDALONE DRYER FOR REUSABLE ITEMS - 600 mm stand alone dryer for pass through units for the quickest turnaround with minimal footprint. Upper air blades designed to hit and dry the top surface of trays and different items.
- AS8 LI - STANDALONE DRYER FOR REUSABLE ITEMS- 800mm stand alone dryer for pass through units for the quickest turnaround with minimal footprint. Upper and lower air blades designed to hit and dry the complete surface of the cups, trays and reusable containers.
- Special voltages

YCXL R

TECHNICAL DATA

EXTERNAL SIZE	725x740x1630 (AxBxC)mm
EXTERNAL SIZE WITH CRC2	725x740x2000 (AxBxC) mm
OVERALL SIZE	2200 (D) mm
CLEARANCE	520 (E) mm
RACK SIZE	600x500 mm
ELECTRICAL SUPPLY	230V/3/50Hz; 400V/3N/50Hz
WASH PROGRAM LENGHT	48/90/120/240/150 "
MAX OUTPUT - WARM WATER CONNECTION (55 C°)	75/40/30/15/24 racks/h
MAX OUTPUT - COLD WATER CONNECTION (15 C°)	35/35/30/15/24 racks/h
RINSE WATER CONSUMPTION	2,7 l
TANK HEATER ELEMENT	2,5 kW
BOOSTER HEATER ELEMENT	7 kW
TANK SIZE	42 l
WASH PUMP	2,2 kW
INSTALLED LOAD	11,7 kW
NOISE	69 dB(A)
WEIGHT	145 kg

YCXL R

TECHNICAL DRAWINGS

The stated values may deviate depending on installation conditions and items washed.
Comenda Ali Group srl reserves the right to modify product specifications at any time without prior notice.

YCXL R

TECHNICAL DRAWINGS









The stated values may deviate depending on installation conditions and items washed.
Comenda Ali Group srl reserves the right to modify product specifications at any time without prior notice.